



DC12V output to power camera !

Battery pack for field monitor use included !

On screen battery indicator and video level statement !

MODEL NUMBER

K-3.5LCD

DESCRIPTION

LED backlight provides longer life,uses less power and provides better color saturation

Battery pack for field monitor use included

Ideal for trouble shooting system setup/fault location

Manual color adjustment

Low power consumption

Case made of durable ABS plastic

Battery pack provides 7 hrs continuous operation when power out closed

Snap-on battery pack holds 4pcs of AA Ni-MH rechargeable batteries (batteries included)

Manual controls for brightness,color,contrast and audio volume

DC12V output to camera for emergency working !

Feature

Monitors for testing video performance, angle of view, and focus of security cameras during installation

With portable carrying wrist strap, rechargeable battery

Can be taken on installer's arm for easier video check

Optional Accessories

Custom Toolbag



SPECIFICATION

Display area	3.5" TFT LCD active matrix
resolutions	320*240
Input signal level	1.0 V P-P 75ohm
Back light type	LED
Brightness	300cd/,m ²
Contrast ratio	150:1
Viewing angle	(up/down/left/right): 40/60/60/60 degree
system of signal	PAL/NTSC
Power requirements	12V DC / 50-60Hz
Power output	DC12V
Power consumption	1.5 w

Actual visible screen size	70.08(H) * 52.56 (V)
operating temperature	-10°C ~ +60°C
Storage temperature	-20°C ~ +70°C

Rear Connection

3.5mm A/V IN / OUT with cables

DC12V output jack

USB 5pins DC in jack

dimmention	119(L)*84(W) * 28(H) (mm)
Packing size	260(L)* 145(W) * 63(H)(mm)
Weight	net weight:120g / gross weight :0.86kg

Carton box info.

25pcs/carton

22kg/carton

Carton size: 540*470*290 (mm)

Hand-Free



Desk Stand

